

Siemens Digital Point Pickup Module



The Siemens Digital Point Pickup Module (PPM) is a slave I/O device that communicates on a P1 FLN or expansion bus. The PPM allows primarily digital point expansion for any APOGEE field panel that has P1 FLN or expansion bus capabilities.

Features

- 1 AI/DI (configurable to 10K Ω Type II NTC thermistor analog input or dry contact digital input via a slide switch), 3 dry contact digital inputs and 2 digital outputs. Total of 6 available points.
- Default communication at 4800 baud also supports 9600, 19200, 38400, 57600 and 115200 via auto-detect.
- 8-bit DIP switch to configure address

- Recover and resume communication on the network after a power interruption without operator intervention.
- Capable of mounting on various electrical junction boxes without field modification or adaptors.
 - 100 mm x 100 mm x 25 mm Asia Pacific standard box, 86 mm x 86 mm x 25 mm China standard box, 4 in. x 4 in. standard depth US box.
- Plenum rated, no enclosure necessary.
- A removable barrier is integrated into the packaging to keep high voltage wiring separate from low voltage wiring within the junction box
- LEDs visible through the housing, indicate the power, communication, and DO status.
- Assembly has a cover label associated with the LEDs for easy labeling.
- No calibration required, thereby reducing maintenance costs.
- Optional DIN Kit for mounting PPM on a DIN rail (PPM-DINKIT) sold separately.

Hardware

Controller Board

The controller interfaces with but does not provide direct control of the following external devices:

- Temperature sensors (room, duct, immersion, and outside air) 10K Ω Type II NTC
- Digital input devices (dry contacts from motion sensors, alarm contacts) or LPACI
- Digital output devices (fans, pumps, stages of electric heat)

Digital Point Pickup Module Specifications

Power Requirements	Input power range of 19.2 Vac to 28.8 Vac (50 or 60 Hz)
Operating Range	
Power Consumption	4 VA
Inputs	
Analog	1 Configurable 10KΩ Type II NTC Thermistor
Digital	3 Fixed dry contact or LPACI and 1 Configurable dry contact or LPACI
Outputs	
Digital	Two Form A NO (Normally Open) Relays with a shared common. 24 to 250 Vac, 3A resistive, 2A General Purpose, 3(2)
Temperature Monitoring Accuracy	±0.25°F over a range of 55°F to 95°F (13°C to 35°C)
NOTE: PPMs have a hard coded range, if the value goes below 20°F (-6.7°C) or above 120°F (48.9°C), the point will display FAILED.	
Dimensions	4.5 in x 4.5 x 1.4 in (114.3 mm x 114.4 mm x 34.5 mm)
Weight	0.5 lb
Communications	
Remote	4800 to 115200 bps FLN Trunk
Local	None
Storage Temperature	-40°F to 158°F (-40°C to 70°C)
Operating Temperature Range	32°F to 122°F (0°C to 50°C) 5% to 95% rh (non-condensing)

Agency Listings	UL 916, PAZX, PAZX7
UL Listing	Canadian Standards C22.2 No. 205
cUL Listed	
FCC Compliance	Part 15 Class B CISPR 22 Class B RCM conformity EU conformity (CE)

Environmental Compliance	Meets EU RoHS Requirements WEEE Compliant
OSHPD Certification	Product meets OSHPD Special Seismic Preapproval certification (OSH-0217-10) under California Building Code 2010 (CBC2010) and International Building Code 2009 (IBC2009) when installed within Siemens enclosure part numbers; PXA-ENC18, PXA-ENC19 or PXA-ENC34.

Product Ordering Information

Description	Product Part Numbers
Digital Point Pickup Module (Asia Pacific Version with Fixed Terminal Blocks)	PPM-1U32.PPF
Point Pickup Module DIN Kit (Kit includes 10 mounting brackets and 10 screws, capable of mounting up to 5 PPMs)	PPM-DINKIT

Information in this document is based on specifications believed correct at the time of publication. The right is reserved to make changes as design improvements are introduced. Product or company names mentioned herein may be the trademarks of their respective owners.
© 2013 Siemens Industry, Inc.